STATIONARY **CONCRETE PUMP**

ETP490



General Dimension

Overall length	4,520mm
Overall width	1,960mm
Overall height	2,220mm
Total weight	3,200kg

Pumpable Reach

Theoretical Vertical Reach		
Piston side	130m	
Theoretical Horizontal Reach		
Piston side	250m	

Engine

Deutz
TD226B-4, 4 cyl. in line
80kW at 2,500rpm
391 Nm at 1,500rpm
4.154 lit
105 x 120mm
Water cooled
24V

Service Refill Capacities

Fuel tank	90L
Hydraulic oil tank	240L
Change interval	500hours
Fuel consumption	226g/kW.h at 2,500rpm

Hydraulic Pump

Main pump type	Kawasaki K3V112
Main pump capacity	No. 1 x 85cc/rev
Main pump pressure	350kg/cm ²
Accumulator pump	Rexroth A10V28

Concrete Drive

Max. Theoretical Concrete Output	
Piston side	40m³/hr at 85 bar
Drive cylinder	dia. 80 x L1,000mm
Concrete cylinder	dia. 150 x L1,000mm
Transfer	S-tube, S1512
	(dia. 150mm-125mm)

Features

Outrigger	
Rear	Manual jack support
ricai	Mariaar jack Support
^	One from moneyal inch
Aux support	One front manual jack
Axle	1 axle & 2 single tires
Water pump	Optional
Water tank	No application
Hopper	EZ Clean Type, 300L
Hopper lubrication	Manual greasing port
Agitator motor	Single motor on hopper
Remote control	Optional, wire or wireless

^{*} Technical amendments are reserved. The specifications are subject to change with or without prior notice.